



**MASONS**  
Designed Smart, Built Tough.

# Barricade FR

## Fire Retardant Building Wrap



A Barricade FR is a fire retardant building wrap suitable for all frame and cladding systems with or without cavity. It is Codemark Certified.

### QUALITY BUILDING WRAP

#### High-quality synthetic material

A non-woven fire retardant, water resistant, breathable synthetic wall underlay for use under direct fixed and non-direct fixed wall cladding on timber framed and steel framed buildings. For use up to and including 'high' wind zones.

### RESISTS UV EXPOSURE

#### High UV Qualities

Manufactured from high quality synthetic spun bonded material with high UV qualities to resist UV exposure for up to 60 days.



**CODEMARK™**  
CM70072



#### **FIRE RETARDANT**

With unique anti-fungal properties



#### **RESISTS UV EXPOSURE**

For up to 60 days

YOUR  
LOGO

#### **CUSTOM BRANDING**

Call your Masons Rep for details

## APPLICATIONS

- To be used where a fire retardant wrap is required. It performs well with all cladding systems and over timber or steel framing.
- Barricade FR is absorbent and can be used with absorbent and non-absorbent cladding.
- Strong and durable. Suitable for all areas of New Zealand including up to 'Very High' wind zones of NZS 3604 and "Extra High" over rigid wall underlays.
- Suitable as a non rigid backing for stucco plaster.
- Suitable as an air barrier on walls that are not lined.
- Can be used on gable ends.
- Vertical use only. Not suitable as a roof underlay.

## NEW ZEALAND BUILDING CODE STANDARD (NZBC)

The following tests have been carried out in accordance with NZBC Acceptable Solution E2/AS1 Table 23:

- Tensile strength, edge tear resistance and resistance to water vapour transmission in accordance with ASNZS 4200.1.
- Resistance to water penetration in accordance with AS/NZS 4201.1.4
- Surface water absorbency in accordance with AS/NZS 4201.6.
- Air resistance to BS 6538.3.
- Shrinkage in accordance with AS/NZS 4201.3.
- pH of extract in accordance with AS/NZS 1301.421.
- Fire retardant in accordance with AS1530 Part 2 Flammability.

## CUSTOM BRANDED WRAP

Barricade FR is available custom branded with your logo. Printed in black or one specified PMS colour. A perfect way to give your company brand exposure.

- Custom Branded BFR is available by the pallet
  - Number of rolls to a pallet: 64
  - Minimum order: 1 pallet
  - Number of colours: 1
  - Rows of logos: 3
  - Lead time: 12-16 weeks
  - All orders are shipped on arrival.
- No stock is held by Masons.

Logos to be supplied by the client.

A Guide to Supplying Logos for BFR is available from your Masons Rep.



| Description  | Masons Code    | Size of Roll               |
|--|----------------|----------------------------|
| Barricade FR Building Wrap 2.74m x 50m <sup>2</sup>  | BFRMPB2.74x50  | 2.74m x 50m <sup>2</sup>   |
| Barricade FR Building Wrap 2.74m x 100m <sup>2</sup> | BFRMPB2.74x100 | 2.74m x 100m <sup>2</sup>  |
| Barricade FR Building Wrap 1.37m x 100m <sup>2</sup> | BFRMPB1.37x100 | 1.37m x 100m <sup>2</sup>  |
| Barricade FR Building Wrap 1.37m x 50m <sup>2</sup>  | BFRMPB1.37x50  | 1.37m x 50m <sup>2</sup>   |
| Barricade FR Building Wrap 1.37m x 25m <sup>2</sup>  | BFRMPB1.37x25  | 1.37m x 25m <sup>2</sup>   |
| Barricade FR Soffit Wrap 0.6m x 21.9m <sup>2</sup>   | BFRMPB0.6x22   | 0.6m x 21.9m <sup>2</sup>  |
| Custom Branded Barricade FR                          |                |                            |
| BFR Building Wrap 2.74m x 36.5m <sup>2</sup>         | tbc on order   | 2.74m x 36.5m <sup>2</sup> |